



Floors, Interior; Carpet over Wood Subfloor with 1/4" Sound Control Mat

PRODUCT ASSEMBLY

1. Hacker TopCoat®SP

An acrylic-based, film forming surface preparation agent.

2. (a) FIRM-FILL® Gypsum Concrete

Has compressive strength up to 2000 psi (ASTM C472).

(b) FIRM-FILL® 2010

Has compressive strengths from 1950-2750 psi (ASTM C472).

(c) FIRM-FILL® 3310


Has compressive strengths from 2000-3300 psi (ASTM C472).

3. Hacker Floor Primer

A rewettable latex primer that is diluted: 1 part Hacker Floor Primer to 4 parts water.

Note

Some installation methods and components are not referenced. Please consult all approved resources to ensure a complete assembly.



When installing carpet over FIRM-FILL® Brand Gypsum Concretes:

General Recommendations:

Hacker Floor Underlayments can be used with many different carpets, carpet pads and adhesives. Follow the recommended guidelines on page 1 of Hacker Industries' "Guidelines for Installing Finished Floor Coverings" to prepare the underlayment.

For Glue-down and double glue-down attachment of carpet and pad, follow the recommended guidelines on page 1 to prepare the underlayment. Follow manufacturers recommendations for adhesives. Prior to installation, the flooring installer shall conduct a sample test to confirm bond compatibility.

Glue-Down Attachment of Tackless Strips over Wood Subfloors:

Prior to installation, the flooring installer should conduct a sample test to confirm bond capability. The following adhesives have been compatible with Hacker Floor Underlayment:

For free-lying carpet modules, Hacker Industries, Inc. strongly recommends that all Hacker Floor Underlayments be sealed prior to installation. Install the carpet modules with 100% adhesive coverage. Follow the recommendations of the carpet modules manufacturer.

- Roberts 0167 Carpet Gripper Cement
- Hydroment 900, manufactured by Bostik
- Polyseamseal® All-Purpose Adhesive Caulk, manufactured by Darworth Co.

For further questions refer to Hacker Industries' Guidelines for Installing Finished Floor Coverings."

HACKER INDUSTRIES, INC.
1600 Newport Center Drive
Newport Beach, CA 92660

PHONE
(949) 729-3101

WEB
www.hackerindustries.com
info@hackerindustries.com