

Floor/Ceiling, Steel Joist w/ Corrugated Deck

REFERENCE: FIRM-FILL® CMD

PRODUCT ASSEMBLY

1. Hacker TopCoat®SP

An acrylic-based, film forming surface preparation agent.

2. FIRM-FILL®CMD


Has compressive strength minimum 3500 psi (ASTM C472).

3. Hacker Floor Primer

A rewettable latex primer that is diluted: 1 part Hacker Floor Primer to 4 parts water.

Note

Some installation methods and components are not referenced. Please consult all approved resources to ensure a complete assembly.



General Notes:
CORRUGATED METAL DECK SYSTEM

1, 1-1/2, and 2 hour UL Design Nos.
G565, G568

Notes:

- 1.) Installation to be completed per manufacturer's specifications
- 2.) Do not scale drawings
- 3.) Contractors Note: for product and company information, visit www.CADdetails.com or www.HackerIndustries.com

When installed over steel truss, FIRM-FILL® CMD provides an economical lightweight solution for multi-family and mid-rise commercial applications. FIRM-FILL® CMD achieves excellent fire and sound ratings while providing a superior crack-resistant surface for the installation of finished floor coverings.

Steel Joist w/ Corrugated Steel Deck

1-2 hr	9-1/4" Deep	G565, G568
1-2 hr	Vulcraft	G561

HACKER INDUSTRIES, INC.
1600 Newport Center Drive
Newport Beach, CA 92660

PHONE
(949) 729-3101

WEB
www.hackerindustries.com
info@hackerindustries.com